

SERIE KORAL / KORAL SERIES
MODELO KS / KS MODEL

Conexión: asp./Imp. 2"ó 50/63 mm. / Connection: inlet / outlet 2" or 50/63 mm.

MODELO / MODEL		P2* HP	P1* KW	MOTOR MEC.	CAUDAL* l/h. FLOW*	PESO kg. WEIGHT	VOLUM. m ³ VOLUME	UDS. Caja / Box QTY.
MONOFÁSICA SINGLE-PHASE 230V	TRIFÁSICA THREE-PHASE (1)							
KS 33 M.B		0,33	0,45	63	4.800	11,2	0,056	1
KS 50 M.B	KS 50 T1.B	0,50	0,58	71	7.500	12,5	0,056	1
KS 75 M.B	KS 75 T1.B	0,75	0,75	71	11.500	13,5	0,056	1
KS100 M.B	KS100 T1.B	1,00	1,00	71	15.400	14,0	0,056	1
KS150 M.B	KS150 T1.B	1,50	1,60	80	21.900	16,5	0,056	1
KS200 M.B		2,00	1,92	80	25.700	17,5	0,056	1
	KS200 T1.B	2,00	1,92	80	25.700	17,0	0,056	1
KS300 M.B		3,00	2,60	90	29.500	22,5	0,056	1
	KS300 T1.B	3,00	2,60	80	29.500	22,0	0,056	1

*CAUDAL: En litros / hora a 10 m.c.a. *FLOW: In liters / hour at 10 meters head.